

BRUSH HAWG®

C-MODEL (MULTI-LEVER)



**Shown with optional equipment*

STANDARD FEATURES

- Heavy Duty 30" Diameter Slewing Ring Bearing
- 2-Stage Planetary Gear Box and Disc-Valve Motor
- 20'-8" Overall Reach
- Boom Designed to Enhance Below Grade Reach
- Dual Stand-Up Operator Stations w/ Multi-Lever Controls
- 4-Way Adjustable Stabilizers w/ Dual Holding Valves on Vertical Cylinders
- 48" x 60" Bucket
- 15 Ton Scissor Hoist
- 5 Micron Synthetic Drop-In Return Filter
- 18' Dump Body w/ 24" Walk-Through



Multi-Lever
Controls



Bolt-On Bucket Cylinder
Covers & Reversible
Bolt-On Bucket Edges



Tip Boom
Hose Retract Box



BRUSH HAWG®

P.O. Box 1527 ♦ Easley, South Carolina 29641
2266 Powdersville Road ♦ Easley, South Carolina 29642

1-800-654-1752 ♦ Fax: (864) 306-3775

Email: sales@brushhawg.com ♦ Website: www.brushhawg.com

All designs and specifications are subject to change at the manufacturer's sole discretion at any time without notice. The data published herein is informational in nature and should not be misconstrued to warrant suitability of the unit for any purpose as performance may vary with the conditions encountered. Products must be installed and operated with all applicable standards, codes, regulations, and recommended safety procedures.