

## Low Maintenance Features



Light weight Nylatron® bushings replace traditional heavy and more costly steel bearings.



Maximum of only four grease fittings makes lubricating quick and easy.



Featuring Nylatron® non-lube wear guides—horizontal slide guides are replaceable without track disassembly.



Hydraulic lines are neatly contained and tucked away during arm retraction.



322 Lavansville Road  
Somerset, Pennsylvania 15501  
814-445-5866 • FAX 814-443-4966  
email gerrym@g-sproducts.com  
www.g-sproducts.com



G-S Products  
Preferred  
Partner Program

**Schedule an on-site demonstration for your routes. DEMO HOT LINE: 877-445-4499**

ASK US ABOUT

**9000series**  
**2YEAR**  
**PEACE OF MIND**  
**WARRANTY**

\*see full warranty for specific details



**SPECIFICALLY DESIGNED TO CONQUER TIGHT ROUTE CONDITIONS**

**True 12 Foot Arm Reach  
Narrow Gauge Lift Design**



**Featuring one of the Lightest, Narrowest and Longest Reach Lift Arms in the Industry**

**We think you will agree, the CS9000 is the most energy efficient, highly productive and versatile Automated Side Loader (ASL) in the industry.**

The CollecStar CS9000's long reach and narrow lift system is exclusively available with our route-proven horizontal eject unload body. This safe and stable arm system is designed with an easy-to-maintain lift/dump motion. Other low maintenance features include a simple electrical system that requires no air limit, or proximity switches on lift mechanism. There is no need for PLC or computer control of lift or packer.



**Constructed for Maximum Durability**

The CS9000 features our route-proven continuous pack, eject unload, non-telescopic body platform on a straight frame chassis. Versatile container-friendly design for 32, 48, 64 and 96 gallon containers. Available with a 3.8 to 6 cubic yard hopper (6 cubic yard/minute displacement at 1200 R.P.M.) with a cover/crusher panel.

**Easy to Maintain**

The CS9000 offers a cost effective single section cast iron gear pump (17 G.P.M. at 700 R.P.M.) or optional 34 G.P.M. tandem section gear pump for dense routes. Nylatron® non-lube wear guides on horizontal slides (replaceable without track disassembly).

**Maximum Productivity and Safety**

Low container dump height under 13' 6" with a shrouded hopper to reduce blown debris. Lift arm horizontal and vertical supports are centered in relationship to the hopper and the load to be lifted — this means less wear and fewer parts to be replaced. L.E.D. body and work lights along with up to four optional cameras for operator safety and ease-of-operation.

**Reduced Fuel Consumption**

Fuel efficient engine idle operation of lift saves not only fuel but engine wear. Meeting today's environmental concerns with an optional Compressed Natural Gas (CNG) model or a hydraulic drive hybrid.

**Best Payload for Supreme Productivity**

Our unique body is designed to collect more and meet legal payloads. It's also designed for safe and easy horizontal unloading without the need for multi-stage cylinders.



Our handy refuse tray offers a convenient 24" maximum loading height for bags and loose materials—a great asset for stops with no carts.



A 38" straight vertical lift before the cart tips allows for easy collection off of retaining walls and snow banks.



**Designed, engineered and built for ease of operation and maintenance**

Available in:

- 13 to 37 Cubic Yard Capacity on Single Stream Body
- 24 to 38 Cubic Yard Capacity on 60/40 Split Body



Fast cycle times, continuous packing and a 50 degree minimum dump angle



Easy access hopper door (single axle model)



Safe horizontal ram eject unloading eliminates costly multi-stage cylinders



Hardox® wear plates and secondary reinforced welds



Easy access hopper ladder (tandem model)